



Allco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

1. Identification of Substance & Company

Product

Product name	JM Single Ply Primer (Low VOC)
Product code	NA
HSNO approval	HSR002662
Approval description	Surface Coatings and Colourants (Flammable) Group Standard 2020
UN number	1133
Proper Shipping Name	ADHESIVES
DG class	3
Packaging group	II
Hazchem code	3YE
Uses	Adhesive

Company Details

Company	Allco Waterproofing Solutions	
Address	5 Te Kia Place Albany Auckland New Zealand	PO Box 101-903 North Shore City 0745 New Zealand
Telephone	+64 9 448 1185	
Website	www.allco.co.nz	

Emergency Telephone Number: 021 441 329

2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020), and is classified as follows:

Classes	Hazard Statements
Flammable liquid cat 2	H225 - Highly flammable liquid and vapour.
Aspiration cat 1	H304 - May be fatal if swallowed and enters airways.
Skin irritation cat 2	H315 - Causes skin irritation.
Eye irritation cat 2	H319 - Causes serious eye irritation.
Reproductive toxicity cat 2	H361 - Suspected of damaging fertility or the unborn child.
STOT RE cat 2	H371 - May cause damage to organs through prolonged or repeated exposure.
STOT SE cat 3	H336 - May cause drowsiness or dizziness.
Aquatic chronic cat 2	H411 - Toxic to aquatic life with long lasting effects.

SYMBOLS

DANGER



Other Classifications

This substance contains <1% quartz (crystalline silica). If the dried primer is sanded and very fine dust is generated the following classification in addition to the above:

Carcinogenicity cat 1	H350 - May cause cancer if inhaled.
STOT RE cat 1	H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read label before use. P201 - Obtain special instructions before use.
------------	--



Alco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

	P202 - Do not handle until all safety precautions have been read and understood.
	P210 - Keep away from ignition sources. No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 - Wash hands thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/eye protection.
Response	P308+P313 - IF exposed or concerned: Get medical advice/ attention.
	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
	P331 - Do NOT induce vomiting.
	P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
	P332+P313 - If skin irritation occurs: Get medical advice/ attention.
	P362 - Take off contaminated clothing and wash before re-use.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
	P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.
	P391 - Collect spillage.
Storage	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
Disposal	P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
4-Chlorobenzotrifluoride	98-56-6	50-100%
Toluene	108-88-3	10-25%
Quartz (SiO ₂)	14808-60-7	0-1%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Recommended first aid facilities Ready access to running water is required. Accessible eyewash is required.

Exposure

Swallowed	IF SWALLOWED: do not induce vomiting, contact a doctor immediately. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before re-use.
Inhaled	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically.



Alco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

5. Firefighting Measures

Fire and explosion hazards:	Vapours may form an explosive mixture in air which can be ignited by many sources such as pilot lights, open flames, electrical motors, switches and static electricity.
Suitable extinguishing substances:	Carbon dioxide, extinguishing powder, foam, fog sprays.
Unsuitable extinguishing substances:	Unknown.
Products of combustion:	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	3YE

6. Accidental Release Measures

Containment	If greater than 1000L is stored, secondary containment and emergency plans to manage any potential spills must be in place.
Emergency procedures	In the event of spillage alert the fire brigade to location and give brief description of hazard. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust on concentrate. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If this occurs contact your regional council immediately).
Clean-up method	Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Disposal	Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage	Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10. Location test certificates must be available if storing >500L. Containers (and outer packaging) must bear the prescribed labelling, including the Hazchem code, UN number, flammability warning and name of contents.
Handling	Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Exposure Stds	Ingredient	WES-TWA	WES-STEL
	4-Chlorobenzotrifluoride	data unavailable	data unavailable
	toluene	50ppm, 188 mg/m ³ (skin)	data unavailable
	Quartz (SiO ₂)	0.05mg/m ³ (respirable dust)	data unavailable

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.



Alco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

Personal Protective Equipment

General

Personal Protective Equipment (PPE) should not be used as the primary means of exposure protection, except in the event of an accident or emergency situation or where all other means of protection have proven to inadequate. Clean PPE after use or dispose of as appropriate. Store PPE for re-use in a clean place. Regular training on the correct use of PPE should be provided. In particular the correct fitting and use of respirators and where applicable the cleaning of respirators should be undertaken.

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin



Protective gloves are recommended. Nitrile gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use. Protective clothing must comply with AS 2919, AS3765.1 or AS3765.2. PVC or rubber boots must comply with AS/NZS 2210.2 and selected and maintained in accordance with AS/NS2210.1.

Respiratory



A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge and a dust/mist filter. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance	colourless liquid
Odour	characteristic odour
pH	no data
Vapour pressure	29hPa (20°)
Viscosity	no data
Boiling point	111°C
Volatile materials	no data
Freezing / melting point	no data
Solubility	insoluble in water
Specific gravity / density	1.2g/cm ³
Flash point	7.2°C
Danger of explosion	no data
Auto-ignition temperature	no data
Upper & lower flammable limits	LEL: 1.2%, UEL: 7.0%
Corrosiveness	non corrosive

10. Stability & Reactivity

Stability	Stable under normal use and storage conditions.
Conditions to be avoided	Flammable substance. Keep away from sources of ignition at all times. Containers should be kept closed in order to avoid contamination.
Incompatible groups	Flammable liquids are incompatible with explosives, flammable gases, flammable solids, oxidising materials.
Substance Specific Incompatibility	Acids, bases.
Hazardous decomposition products	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Nitrogen, and under some circumstances, oxides of nitrogen. Water.
Hazardous reactions	No specific hazards.



Allco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

11. Toxicological Information

Summary

IF SWALLOWED: aspiration into the lungs, when swallowed or vomited may cause chemical pneumonitis which can be fatal. May cause gastrointestinal irritation.

IF IN EYES: direct contact may be irritating to the eyes, vapours may also be irritating.

IF ON SKIN: may be irritating to skin. Solvent may dry out the skin leading to cracking.

IF INHALED: vapours may cause dizziness and drowsiness if inhaled.

CHRONIC: Toluene vapours may cause reversible damage to kidneys and liver. Prolonged exposure can cause nerve damage (CNS). Toluene may cause damage to foetus possible fetotoxicity, paternal effects. Toluene may cause ototoxicity.

CHRONIC: this product does contain crystalline silica, inhalation of respirable dusts has been linked to silicosis and lung cancer. Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). See carcinogenicity and systemic toxicity below.

Supporting Data

Acute	Oral	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is >5,000 mg/kg. Data considered includes: 4-Chlorobenzotrifluoride 5546 mg/kg (rat), toluene 636 mg/kg (rat).
	Dermal	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (dermal, rat) for the mixture is >5000 mg/kg. Data considered includes: 4-Chlorobenzotrifluoride >3300mg/kg (rabbit).
	Inhaled	Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is >20mg/L. Data considered includes: 4-Chlorobenzotrifluoride > 32.03 mg/l (rat), toluene 12.5 - 28.8 mg/l (vapour, rat).
	Eye	The mixture is considered to be an eye irritant, because some of the ingredients (4-Chlorobenzotrifluoride, toluene) present are considered eye irritants in more concentrated form.
	Skin	The mixture is considered to be a skin irritant, because some of the ingredients present are considered skin irritants (4-Chlorobenzotrifluoride, toluene) in more concentrated form.
Chronic	Sensitisation	No ingredient present at concentrations > 0.1% is considered a sensitizer.
	Mutagenicity	No ingredient present at concentrations > 0.1% is considered a mutagen.
	Carcinogenicity	This mixture does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of mortar). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer
	Reproductive / Developmental	The mixture is considered to be a suspected reproductive or developmental toxicant. Toluene is suspected to be a reproductive or developmental toxicant. Octamethylcyclotetrasiloxane may have effects on the foetus and cause reproductive disorders on tests with laboratory animals.
	Systemic	The mixture is considered to be a suspected target organ toxicant, toluene is classed 6.9B by EPA. Chronic overexposure to aliphatic hydrocarbons can cause loss of coordination, reduction in reaction times and central and peripheral nervous system damage (n-Hexane). This substance may cause dizziness and drowsiness.
	Aggravation of existing conditions	None known.

12. Ecological Data

Summary

This mixture is toxic towards aquatic organisms with long lasting effects.

Supporting Data

Aquatic	Using EC ₅₀ 's for ingredients, the calculated EC ₅₀ for the mixture is between 1 mg/L and 10 mg/L. Data considered includes: 4-Chlorobenzotrifluoride LC ₅₀ : 3mg/L (96h, Danio rerio (zebra fish)), EC ₅₀ : 2mg/L (48h, Daphnia magna), NOEC: 0.41mg/L (72h, Pseudokirchneriella subcapitata (green algae)), Toluene 5.8 mg/l (96hr, Oncorhynchus mykiss), 11.5 mg/l (48hr, Daphnia magna), 12.5mg/L (72hr, Algal)
Bioaccumulation	No data
Degradability	Not readily biodegradable



Alco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

Soil	No data available for the mixture. The soil toxicity value for the mixture is estimated to be ≥ 100 mg/kg.
Terrestrial vertebrate	This product is not considered harmful to terrestrial vertebrates. No LC ₅₀ (diet) data for ingredients are available and the classification is based on the LD ₅₀ (oral) – see section 11 – oral toxicity.
Terrestrial invertebrate	The mixture is not considered harmful to terrestrial invertebrates.
Biocidal	Not biocidal.
Environmental effect levels	No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

UN number:	1133	Proper shipping name:	ADHESIVES
Class(es)	3	Packing group:	II
Precautions:	Flammable liquid	Hazchem code:	3YE

IMDG

UN number:	1133	Proper shipping name:	ADHESIVES
Class(es)	3	Packing group:	II
Precautions:	Flammable liquid	EmS	F-E, S-D

IATA

UN number:	1133	Proper shipping name:	ADHESIVES
Class(es)	3	Packing group:	II
Precautions:	Flammable liquid	ERG Guide	128



Allco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020. All ingredients appear on the NZIoC.

Specific Controls

Key workplace requirements are:

SDS	To be available within 10 minutes in workplaces storing any quantity.
Inventory	An inventory of all hazardous substances must be prepared and maintained.
Packaging	All hazardous substances should be appropriately packaged including substances that have been decanted, transferred or manufactured for own use or have been supplied
Labelling	Must comply with the Hazardous Substances (Labelling) Notice 2017.
Emergency plan	Required if > 1000L is stored.
Certified handler	Not required.
Tracking	Not required.
Bunding & secondary containment	Required if > 1000L is stored.
Signage	Required if > 250L is stored in any one location.
Location test certificate	Required if > 100L (containers >5L), 250L (containers ≤5L), 50L (in use) is stored in any one location.
Flammable zone	Must be established if > 100L (closed containers), 25L (decanting), 5L (open occasionally), 1L (in use), stored in any one location is stored in any one location.
Fire extinguisher	If > 250L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code	Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020 Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (New Zealand)
GHS	Globally Harmonised System of Classification and Labelling of Chemicals, 7 th revised edition, 2017, published by the United Nations.
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL	Lower Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
NZIoC	New Zealand Inventory of Chemicals
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
STOT RE	System Target Organ Toxicity – Repeated Exposure
STOT SE	System Target Organ Toxicity – Single Exposure
TWA	Time Weighted Average – generally referred to as WES averaged over typical work day (usually 8 hours)
UEL	Upper Explosive Limit
UN Number	United Nations Number



Allco Waterproofing Solutions

JM Single Ply Primer (Low VOC)

Safety Data Sheet

WES

Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data

Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).

Controls

EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances) Regulations 2017, www.legislation.govt.nz

WES

The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz.

Other References:

EU ECHA, ingredients SDS's, ChemIDplus, Suppliers SDS

Review

Date

October 2017
March 2022

Reason for review

Not applicable – new SDS
5 yearly update, HSNO to GHS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: **+64 21 1040951**.

