

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM Single Ply Primer (Low VOC)

Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1 303-978-2000 8:00 a.m.-5:00 p.m. M-F  
Emergency telephone : 1-800-424-9300 (Chemtrec, in English)  
number

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure  
Specific target organ toxicity : Category 2  
- repeated exposure  
Aspiration hazard : Category 1**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.Precautionary statements : **Prevention:**

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

P201 + P202 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P233 Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	>= 50 - <= 100
toluene	108-88-3	>= 10 - <= 25
quartz (SiO <sub>2</sub> )	14808-60-7	>= 0 - <= 1

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Keep eye wide open while rinsing.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.  
Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Foam  
Dry sand
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

Hazardous combustion products	:	Hazardous decomposition products due to incomplete combustion Carbon oxides Chlorine compounds Fluorine compounds
Specific extinguishing methods	:	Standard procedure for chemical fires.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA
		CEIL	300 ppm	OSHA
		Peak	500 ppm (10 minutes)	OSHA
quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable fraction)	0.025 mg/m3	ACGIH
		TWA (respirable)	10 mg/m3 / %SiO <sub>2</sub> +2	OSHA
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA
		TWA (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection	
Material	: Solvent-resistant gloves
Remarks	: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Eye protection	: Tightly fitting safety goggles Safety glasses with side-shields Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. Written instructions for handling must be available at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Colour	: colourless
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/range	: not determined
Boiling point/boiling range	: 111 °C
Flash point	: 7.2 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7.0 %(V)

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

Lower explosion limit	: 1.2 %(V)
Vapour pressure	: 29 hPa (20 °C)
Relative vapour density	: Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density	: No data available
Density	: 1.2 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides Nitrogen oxides (NO <sub>x</sub> )

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute dermal toxicity	: Acute toxicity estimate : > 2,000 mg/kg Method: Calculation method
-----------------------	---

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

**Acute toxicity****Components:****Benzene, 1-chloro-4-(trifluoromethyl)-:**

Acute oral toxicity : LD50 (Rat): 6,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 33 mg/l  
Exposure time: 4 h

LC50 (Rat): &gt; 4479 ppm

Acute dermal toxicity : LD50 (Rabbit): &gt; 2,700 mg/kg

**Acute toxicity****toluene:**

Acute oral toxicity : LD50 Oral (Rat, male): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): &gt; 12,267 mg/kg

**Skin corrosion/irritation****Components:****Benzene, 1-chloro-4-(trifluoromethyl)-:**

Species: Rabbit

Result: No skin irritation

**Skin corrosion/irritation****toluene:**

Species: Rabbit

Result: Irritating to skin.

**Serious eye damage/eye irritation****Components:****Benzene, 1-chloro-4-(trifluoromethyl)-:**

Species: Rabbit

Result: No eye irritation

**Serious eye damage/eye irritation****toluene:**

Species: Rabbit

Result: Mild eye irritation

Exposure time: 24 h

**Respiratory or skin sensitisation****Components:****Benzene, 1-chloro-4-(trifluoromethyl)-:**

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

Exposure routes: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: May cause sensitisation by skin contact.

<b>IARC</b>	Group 1: Carcinogenic to humans	
	quartz (SiO <sub>2</sub> )	14808-60-7
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	Known to be human carcinogen	
	quartz (SiO <sub>2</sub> )	14808-60-7

**Reproductive toxicity****Components:****toluene:**

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure****Components:****toluene:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure****Components:****toluene:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****toluene:**

May be fatal if swallowed and enters airways.

**Experience with human exposure****Components:****toluene:**

Skin contact:

Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

**Further information****Product:**

Remarks: Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Benzene, 1-chloro-4-(trifluoromethyl)-:**Partition coefficient: n- : log Pow: 3.7 (25 °C)  
octanol/water**toluene:**Partition coefficient: n- : Pow: 2.7  
octanol/water**Mobility in soil**

No data available

**Other adverse effects****Product:**Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).Additional ecological : No data available  
information**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Disposal of residual product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

U.S. Department of Transportation: UN 1133, Adhesives, 3, II.

LIMITED QUANTITY if shipped in inner packagings not over 1.0 L (0.3 gallons) net capacity each, packed in a strong outer packaging.

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D) : The following substance(s) is/are subject to TSCA 12(b) export notification requirements:  
Benzene, 1-chloro-4-(trifluoromethyl)-**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	4000
toluene	108-88-3	100	4000

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene 108-88-3

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

toluene 108-88-3 10 - 25 %

**JM Single Ply Membrane Primer (Low VOC)**

Version 2.2

Revision Date 08/30/2017

Print Date 08/30/2017

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

toluene	108-88-3	10 - 25 %
---------	----------	-----------

**US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)**

toluene	108-88-3
quartz (SiO <sub>2</sub> )	14808-60-7

**US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)**

Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6
toluene	108-88-3
quartz (SiO <sub>2</sub> )	14808-60-7

**US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)**

Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6
toluene	108-88-3
quartz (SiO <sub>2</sub> )	14808-60-7

**US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
---------	----------

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 08/30/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.