

NOTE -
IF USING PLYWOOD
SUBSTRATES EFVM / ILD
LEAK DETECTION
IS REQUIRED

SUBSTRATE
BY DESIGN

JM TPO PROTECTION LAYER (2ND LAYER)
UNDER BALLAST AREA

300mm
ALUMINIUM DRAIN BOX
WITH LID FOR ACCESS

NOTE - ALLOW FOR WET GROWTH MEDIUM WEIGHT OF
100KG PER M2 OF 100MM OF SOIL DEPTH

SLOTTED ALUMINIUM
GARDEN EDGE

VEGETATION

GROWING MEDIA FROM
60MM TO 100MM

ALLCO DRAINAGE LAYER

JM TPO FIELD SHEET (1.5MM)
WITH JM APPROVED ADHESIVE

LAP TAPE

JM SINGLE PLY SEALING
MASTIC PLACED ON FLANGE
PRIOR TO TPO LAP AND CLAMP

AQUAKNIGHT DRAINAGE
OUTLET
(RECOMMENDED)

1

JM TPO - GREEN ROOF - DRAINAGE OUTLET

SCALE: NTS

NOTE -
IF USING PLYWOOD
SUBSTRATES EFVM / ILD
LEAK DETECTION
IS REQUIRED

SUBSTRATE
BY DESIGN

SPECIFIED PAVER ON BUZON
PEDESTALS

SLOTTED ALUMINIUM
GARDEN EDGE

VEGETATION

GROWING MEDIA FROM
60MM TO 100MM

ALLCO DRAINAGE LAYER

JM TPO FIELD SHEET (1.5MM)
WITH JM APPROVED ADHESIVE

LAP TAPE

2

JM TPO - GREEN ROOF - PAVED PERIMETER / JUNCTION

SCALE: NTS



The information and data contained herein are believed to be accurate and reliable.
This information does not constitute a warranty and should be used in conjunction with
the project specification document supplied by Allco Waterproofing Solutions Ltd
Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from
this information.
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:
Web: www.allco.co.nz
Email: info@allco.co.nz
Telephone: 09 448 1185
Facsimile: 09 448 1186



DRAWN BY: ALLCO	DATE: 05/2020
DRAWING REF: T-101	REV: 1