

NOTE
ALLCO WATERPROOFING SUGGESTS
THAT ROOF DRAINAGE BE DESIGNED TO
USE CLAMPED DRAINAGE OUTLETS IN
PREFERENCE TO SCUPPER OUTLETS

JM TPO MEMBRANE
WITH JM APPROVED
ADHESIVE

NOTE - RADIUS EDGES TO
SUSTRATE - 5MM MIN.

JM TPO MEMBRANE
WITH JM APPROVED
ADHESIVE

**JM TPO MEMBRANE
WITH JM APPROVED
ADHESIVE**

HOT AIR WELD TO TPO LAP

JM TPO MEMBRANE APRON

HOT AIR WELD TO TPO SCUPPER

HOT AIR WELD TO TPO LAP / SCUPPER

SUBSTRATE /
CLADDING BY
DESIGN.

SEALING / FLASHING OF SCUPPER TO FACADE - BY BUILDER

TPO SCUPPER

SUBSTRATE
BY DESIGN.

REBATE
SCUPPER FLUSH
TO SUBSTRATE

1

SCUPPER / OVERFLOW

SCALE: NTS



The information and data contained herein are believed to be accurate and reliable. This information does not constitute a warranty and should be used in conjunction with the project specification document supplied by Allco Waterproofing Solutions Ltd. Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from this information.

© Allco Waterproofing Solution Ltd

For Technical Advice Contact:
Web: www.allco.co.nz
Email: info@allco.co.nz
Telephone: 09 448 1185
Facsimile: 09 448 1186



DRAWN BY:
ALLCO

DATE:
17/04/19

DRAWING REF:
T-012B

REV:
2