

CASALI ADERIX
SELF ADHESIVE MEMBRANE

BITUMINOUS PRIMER

PROTECTION /
DRAINAGE BOARD.

150MM
MIN

CASALI OLYMPIA TORCH
ON MEMBRANE TO SLAB.
LOOSE LAID WITH
TORCHED LAPS

DRAINAGE COIL.
WITH DRAINAGE
MATERIAL AS SPECIFIED

NOTE - WALL MEMBRANE OPTIONS:

CASALI OLYMPIA MEMBRANE CAN BE
SUBSTITUTED FOR CASALI ADERIX
MEMBRANE.

1

RETAINING WALL / FLUSH FOOTING JUNCTION

SCALE: NTS

150MM
MIN

CONCRETE SUBSTRATE.
TO BE FLUSH WITH NO
VOIDS.
MASONRY TO BE FLUSH
POINTED

CONCRETE SUBSTRATE.
REFER TO STRUCTURAL
DRAWINGS

ALLSHEET DPM OR SIMILAR.
TAPED TERMINATION.

SITE CONCRETE OR
COMPACTED SAND FINES
ON COMPACTED BASE

2

RETAINING WALL / FLUSH FOOTING JUNCTION

SCALE: NTS

DPM TO FOOTING AND SLAB



The information and data contained herein are believed to be accurate and reliable.
This information does not constitute a warranty and should be used in conjunction with
the project specification document supplied by Allco Waterproofing Solutions Ltd
Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from
this information.
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:
Web: www.allco.co.nz
Email: info@allco.co.nz
Telephone: 09 448 1185
Facsimile: 09 448 1186



DRAWN BY:
ALLCO

DATE:
07/2023

DRAWING REF:
CA-PS-02

REV:
1