

2 LAYERS OF ASPHALT
(32mm THICK MIN EACH LAYER)

XPS INSULATION

CONCRETE SUBSTRATE BY DESIGN

HYDROTECH MM6125 MEMBRANE SYSTEM

PMR ROOF / ASPHALT

2 LAYERS OF ASPHALT
(32mm THICK MIN EACH LAYER)

32
32

CONCRETE SUBSTRATE BY DESIGN

HYDROTECH MM6125 MEMBRANE SYSTEM

COLD ROOF / ASPHALT

2 LAYERS OF ASPHALT
(32mm THICK MIN EACH LAYER)

32
32

COMPACTED HARDFILL

90mm
MIN

CONCRETE SUBSTRATE BY DESIGN

HYDROTECH MM6125 MEMBRANE SYSTEM

COLD ROOF / ASPHALT

HYDROTECH MM6125 MEMBRANE SYSTEM

PROTECTION SHEET

1ST LAYER.

2ND LAYER.

FLEX-FLASH F

CONCRETE SUBSTRATE

1

HYDROTECH - Cold/PMR Roof – Asphalt Options

SCALE: NTS



The information and data contained herein are believed to be accurate and reliable. This information does not constitute a warranty and should be used in conjunction with the project specification document supplied by Allco Waterproofing Solutions Ltd. Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from this information.
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:
Web: www.allco.co.nz
Email: info@allco.co.nz
Telephone: 09 448 1185
Facsimile: 09 448 1186



DRAWN BY:
ALLCO

DATE:
06/19

DRAWING REF:
H-020B

VER:
1.2