

VOLCLAY VOLTEX BONDED TO PRECAST PANEL

WATERSTOPPAGE TO VOID 300mm ABOVE F.G.L WITH SEALANT TO TOP LEDGE

ALLCO ALLGUARD PROTECTION BOARD

PRECAST CONCRETE WALL

WATERSTOPPAGE GRANULES OR BENTOSEAL OVER PEF ROD

VOLCLAY VOLTEX. 300MM STRIP OVER JOINT

SEALANT ON PEF ROD

SEALANT ON PEF ROD

300MM LAP

NOTE  
VOLTEX IS GENERALLY RECOMMENDED TO BE BONDED / PRE-APPLIED TO THE PRECAST PANEL IN THE FORMING YARD. IT CAN BE SITE APPLIED BUT SHOULD BE BACK FILLED PROMPTLY - WEATHER DEPENDANT. VOLTEX, WHEN PRE-APPLIED, CAN BE EXPOSED FOR LONGER PERIODS

1 PRECAST WALL PANEL BUTT JOINT  
SCALE: NTS  
VOLTEX

1A PRECAST WALL PANEL BUTT JOINT - OPTION  
SCALE: NTS  
VOLTEX

VOLCLAY SWELLTITE. POST APPLIED TO PRECAST WALL PANEL

WATERSTOPPAGE TO VOID 300mm ABOVE F.G.L WITH SEALANT TO TOP LEDGE

ALLCO ALLGUARD PROTECTION BOARD

PRECAST CONCRETE WALL

WATERSTOPPAGE GRANULES OR BENTOSEAL OVER PEF ROD

VOLCLAY SWELLTITE. 300MM STRIP OVER JOINT

SEALANT ON PEF ROD

SEALANT ON PEF ROD

OUTSIDE

INSIDE

NOTE  
SWELLTITE IS SITE APPLIED TO PRECAST PANELS AND SHOULD BE BACK FILLED WITHOUT DELAY.

2 PRECAST WALL PANEL BUTT JOINT  
SCALE: NTS  
SWELLTITE



The information and data contained herein are believed to be accurate and reliable. This information does not constitute a warranty and should be used in conjunction with the project specification document supplied by Allco Waterproofing Solutions Ltd. Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from this information.  
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:  
Web: www.allco.co.nz  
Email: info@allco.co.nz  
Telephone: 09 448 1185  
Facsimile: 09 448 1186



|                        |                |
|------------------------|----------------|
| DRAWN BY:<br>ALLCO     | DATE:<br>06/23 |
| DRAWING REF:<br>V-W-04 | REV:<br>5      |