



NOTE
IF 'WAFFLE' OR RECESSED PODS ARE USED THEN THEY MUST BE FLIPPED UPSIDE DOWN SO FLAT SURFACE IT ON THE MEMBRANE. WHICH WILL INCREASE THE CONCRETE QUANTITY

NOTE
RIB RAFT / POD FLOORS SHOULD USE SOLID PODS. IF NOT REFER ALLCO TECHNICAL DEPARTMENT. COMPACTED SUBSTRATE SHOULD BE FLAT AND LEVEL TO MINIMISE "ROCKING" OF PODS

2

POD TYPE CLARIFICATION

SCALE: NTS

PROPRIETARY INSULATION SYSTEM TO SLAB EDGE. PRE-INSTALLED

INSULATION AS PERMANENT FORMWORK PROVIDES CONFINEMENT TO MEMBRANE

VOLTEX MEMBRANE PLACED TO INSIDE FACE OF EDGE INSULATION. SPIRAL FIXINGS PLACED THROUGH MEMBRANE INTO INSULATION

VOLTEX MEMBRANE LAID TO COMPACTED BASE COURSE.

VOLTEX MEMBRANE CAN BE PLACED UNDER POD FLOOR. CANNOT BE BE PLACED OVER

INDICATIVE 'SPIRAL' FIXING SYSTEM 'TIES' TO POURED SLAB

F.F.L.
50 MM
F.G.L.

1

EDGE INSULATION - POST-APPLIED

SCALE: NTS
RIB RAFT FLOOR SYSTEM

2

PENETRATION - RIB RAFT FLOOR

SCALE: NTS

PIPE LAGGING TO BE PLACED TIGHTLY DOWN TO RX. LAGGING IS TO BE FULLY ADHESIVE FIXED TO PIPE TO ENSURE CONFINEMENT PRESSURE TO AREA ABOVE WATERPROOFING

100 MM MIN

WATERSTOP-RX. SELECT PRODUCT BASED ON COVERAGE AVAILABLE 50-75MM COVER

BENTOSEAL FILLET

WATERSTOPPAGE 6MM MIN



The information and data contained herein are believed to be accurate and reliable. This information does not constitute a warranty and should be used in conjunction with the project specification document supplied by Allco Waterproofing Solutions Ltd. Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from this information. If variances to published CETCO documentation occur, ALLCO detailing takes precedent. © Allco Waterproofing Solution Ltd

For Technical Advice Contact:
Web: www.allco.co.nz
Email: info@allco.co.nz
Telephone: 09 448 1185
Facsimile: 09 448 1186



| | |
|-------------------------|------------------|
| DRAWN BY: ALLCO | DATE: 11/2024 |
| DRAWING REF: V-IN-02 | REV: 1 |