


NOTE - IF WETSEAL SEALANT IS NOT BITUMEN COMPATIBLE IT IS RECOMMENDED TO USE ALLCO BARRIER TAPE AS SEPERATION LAYER.

NOTE - IF WETSEAL AIRSEAL IS REQUIRED SEALANT MUST BE COMPATIBLE WITH BITUMEN BASE PRODUCTS

SUBSTRATE BY DESIGN



FINISH MEMBRANE 100MM MIN. UP FRAMING AT ENDS. WIDTH TO SUIT JOINERY AND CLADDING. REFER E2/AS1 FIG62(B)(D)

SELECTED JOINERY WITH REAR AIR SEAL

SILL SUPPORT BAR WITH SEALED FIXINGS - IF APPLICABLE. PRE-FILL FIXING HOLES WITH SILICONE SEALANT.

CASALI CAP SHEET MEMBRANE

CASALI BASE SHEET MEMBRANE

PRIMER (DERMAPRIMER OR IDROPRIMER)

SUBSTRATE BY DESIGN

ALLCO BITUMEN FILLET OR TIMBER

1

UPSTAND DETAIL - WINDOW REBATE

SCALE: NTS



The information and data contained herein are believed to be accurate and reliable. This information does not constitute a warranty and should be used in conjunction with the project specification document supplied by Allco Waterproofing Solutions Ltd. Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from this information.  
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:  
Web: [www.allco.co.nz](http://www.allco.co.nz)  
Email: [info@allco.co.nz](mailto:info@allco.co.nz)  
Telephone: 09 448 1185  
Facsimile: 09 448 1186



DRAWN BY: ALLCO  
DATE: 05/24

DRAWING REF: CA-002C

REV: 4